

Product Overview Brochure

2016



ANALOG WAY®
Pioneer in Analog, Leader in Digital

LiveCore™ series: Overview

NeXtage 08 - Ref. NXT0802	Power true-seamless AV Processor with 8 scalers
	<ul style="list-style-type: none"> 8 seamless inputs and 28 input plugs 2 outputs Independent Preview/Mosaic/Monitoring output Full live Preview of all sources (Preview/Mosaic/Monitoring) Customization of monitoring layouts (Up to 8 templates stored) 2 true-seamless scaled layers + 1 native background layer per output Advanced Layer management Cut & Fill Features Rotation capability in output (Step by 90°) Ruggedized and heavy-duty design User-friendly & intuitive Graphic Interface (Web RCS) Option: 4K processing upgrade (4K@30Hz 4:4:4)

1 PRW 8 IN 2 OUT 3U size



NeXtage 16 - Ref. NXT1604	Power true-seamless AV Processor with 16 scalers
	<ul style="list-style-type: none"> 4 true-seamless scaled layers + 1 native background layer per output Option: 4K processing upgrade (4K@30Hz 4:4:4)

1 PRW 8 IN 2 OUT 3U size



Ascender 16 - 4K - Ref. ASC1602-4K	Powerful multi-screen seamless Switcher with 16 scalers
	<ul style="list-style-type: none"> 12 seamless inputs and 42 input plugs 4 outputs 2 true-seamless scaled layers + 1 native background layer per output Additive and associative modularity Input format up to 4K@30Hz 4:4:4 on HDMI plug or four quadrant 4K@60Hz 4:2:0 Output format up 4K@30Hz 4:4:4, 4K@60Hz on HDMI plug 4:2:0 and four quadrant 4K@60Hz 4:4:4 4K frames support Heterogenous Link support Independent Output rate

1 PRW 12 IN 4 OUT 4U size



Ascender 32 - 4K - Ref. ASC3204-4K	Powerful multi-screen seamless Switcher with 32 scalers
	<ul style="list-style-type: none"> 4 true-seamless scaled layers + 1 native background layer per output Device temporary downgrade

1 PRW 12 IN 4 OUT 4U size



Ascender 48 - 4K - Ref. ASC4806-4K	Powerful multi-screen seamless Switcher with 48 scalers
	<ul style="list-style-type: none"> 6 true-seamless scaled layers + 1 native background layer per output Option: Perspective Layer upgrade

1 PRW 12 IN 4 OUT 4U size



Vertige™ - Ref. VRC300	Premium Remote Controller for large Events/Multi-venues
	<ul style="list-style-type: none"> User-friendly remote console Fast management of layers and presets Advanced features for events Contextual buttons Large 16/9 TFT color touch screen for preview and configurations Compatible with all LiveCore™ series

LiveCore™ series: Overall Comparison

References	Ascender 48 - 4K Ref. ASC4806-4K	Ascender 32 - 4K Ref. ASC3204-4K	Ascender 16 - 4K Ref. ASC1602-4K	NeXtage 16 Ref. NXT1604	NeXtage 08 Ref. NXT0802
INPUTS					
Universal Analog Input (RGBHV, YUV, Y/C & Composite)	12	12	12	8	8
DVI-I Scaled	6	6	6	6	6
DVI Dual-Link	3	3	3	2	2
HDMI	6	6	6	4	4
DisplayPort	3	3	3	2	2
3G/HD/SD-SDI	12	12	12	8	8
Standard Max resolution	WQXGA/Ultra HD & 4K	WQXGA/Ultra HD & 4K	WQXGA/Ultra HD & 4K	WQXGA/Ultra HD & 4K	WQXGA/Ultra HD & 4K
Universal analog input EDID	Except DVI-A	Except DVI-A	Except DVI-A	Except DVI-A	Except DVI-A
EDID (HDMI - DVI - DisplayPort)	All inputs	All inputs	All inputs	All inputs	All inputs
HDCP compliant & Disable	✓	✓	✓	✓	✓
OUTPUTS					
Program/Output	4	4	4	2	2
Preview on Output 2				✓	✓
Max resolution	WQXGA/ Ultra HD & 4K	WQXGA/ Ultra HD & 4K	WQXGA/ Ultra HD & 4K	2K/WQXGA	2K/WQXGA
Independent Preview/Mosaic/Monitoring Output (Full live Preview all sources)	✓	✓	✓	✓	✓
Video Out 3G/HD/SD-SDI - RGB - RGsB - RGBs - YUV - Y/C - Comp	✓	✓	✓	✓	✓
Monitoring DVI or DVI Dual-Link	✓	✓	✓	✓	✓
HDCP compliant DVI	✓	✓	✓	✓	✓
Independent Output Rate	✓	✓	✓	✓	✓
MULTI-DISPLAY CONFIGURATIONS					
Associative Modularity Via Vertige™ Ref. VRC300 Console (up to 4 units)	✓	✓	✓	✓	✓
Soft Edge H&V: max number of outputs with associative modularity	16	16	16	8	8
Hard Edge H&V: max number of outputs with associative modularity	16	16	16	8	8
Additive Modularity via Web RCS (Link between 2 units only)	✓	✓	✓	✓	✓
Soft Edge H&V: max number of outputs with additive modularity	8	8	8	8	8
Hard Edge H&V: max number of outputs with additive modularity	8	8	8	8	8
PREVIEW					
Full Live Preview of all sources (Preview/Mosaic/Monitoring)	✓	✓	✓	✓	✓
Confidence Monitor	✓	✓	✓	✓	✓
Customizable labels on Monitoring/Preview display	✓	✓	✓	✓	✓
Displaying of widgets in Monitoring/Preview display	12	12	12	8	8
TRANSITIONS & EFFECTS					
True A/B Mix	✓	✓	✓	✓	✓
Transition: Cut, Fade, Slide, Wipe, Circle, Stretch & Depth	✓	✓	✓	✓	✓
Color effects: Black&White, Sepia, Negative, Solarize	✓	✓	✓	✓	✓
Background Cut Effect	✓	✓	✓	✓	✓
Flying Curve Effect	✓	✓	✓	✓	✓
LAYERS					
Number of true-seamless scaled layers per output	6	4	2	4	2
Native Background	✓	✓	✓	✓	✓
Advanced Layers Management	✓	✓	✓	✓	✓
FRAME & LOGO					
Fully resizable (Supporting all settings and layer transitions)	✓	✓	✓	✓	✓
Formats: BMP, JPEG, TIFF, GIF, PNG, ICO	✓	✓	✓	✓	✓
Download/Upload with the Web RCS	✓	✓	✓	✓	✓
Capture from live inputs	✓	✓	✓	✓	✓
Management of pictures via a thumbnail library	✓	✓	✓	✓	✓
Available Frame/Logo memories	100	100	100	100	100
OTHER FEATURES					
Tally/GPI-O	✓	✓	✓	✓	✓
Independent Frame Lock input	✓	✓	✓	✓	✓
HUMAN MACHINE INTERFACE					
Web RCS (Web Based Remote Control Software)	✓	✓	✓	✓	✓
Remote Services	✓	✓	✓	✓	✓
Remote Maintenance Tools	✓	✓	✓	✓	✓
Remote Controller - VRC300	✓	✓	✓	✓	✓
4K HARDWARE					
Number of 4K 30Hz 4:4:4 HDMI inputs	3	3	3	2	2
Max input resolution	Ultra HD & 4K	Ultra HD & 4K	Ultra HD & 4K	Ultra HD & 4K	Ultra HD & 4K
Number of HDMI outputs in 4K 30Hz 4:4:4 mode	2	2	2	1	1
Number of HDMI outputs in 4K 60Hz 4:2:0 mode	1	1	1		
Max output resolution	Ultra HD & 4K	Ultra HD & 4K	Ultra HD & 4K	Ultra HD & 4K	Ultra HD & 4K
PERSPECTIVE LAYERS OPTION					
Reference	OPT-4K-ASC4806-PL				
Number of Perspective Layers per output	3				
FORM FACTOR					
Rugged Design	✓	✓	✓	✓	✓
Enclosure	4RU	4RU	4RU	3RU	3RU
Rack mount kit supplied	✓	✓	✓	✓	✓

Option: OPT-4K-NXT1604 Option: OPT-4K-NXT0802

Midra™ series: Overview

QuickVu 3G - Ref. QVU150-3G	Hi-Resolution Mixer seamless Switcher with 8 inputs
 <ul style="list-style-type: none"> 8 seamless inputs 2 outputs (Program and Preview) 14 input plugs available Capability to switch between any input plugs 1 operating mode: Mixer mode True seamless switching with full preview Ability to modify the program in real time without using the Preview Quick Frame mode Outputs fully resizable 	<ul style="list-style-type: none"> 3G-SDI video output Transitions: Fade, Dissolve, Cut, Wipe & Slide Full audio Digital Compliant on DVI-D & HDMI plugs Advanced Audio Management with the RCS² EDID Management on 6 inputs Ability to read and display the output EDIDs Custom output formats Chroma/Luma Key & Titling

1 PRW 8 IN 2 OUT 2U size



Pulse ² 3G - Ref. PLS350-3G	Hi-Resolution Mixer seamless Switcher with 8 inputs and Native Matrix mode
 <ul style="list-style-type: none"> Up to 2 layers on Frame Background 2 operating modes: Mixer and Native Matrix modes Direct Swap function 	<ul style="list-style-type: none"> Direct Split function Dynamic Layer (Moving from A to B) with Flying, Zooming and Cropping Freeze features (Input/Layer/Screen)

1 PRW 8 IN 2 OUT 2U size



Saphyr - Ref. SPX450	Multi-Layer Hi-Resolution Mixer seamless Switcher with 10 inputs and Native Matrix mode
 <ul style="list-style-type: none"> 10 seamless inputs 16 input plugs available Up to 3 layers on Frame Background Mosaic Preview mode with 2 modes 	<ul style="list-style-type: none"> Video output (CVBS, YPbPr, 3G-SDI) (Zoom 50 to 400%) Capability to crop the Frames and Logos

1 PRW 10 IN 2 OUT 2U size



Eikos ² - Ref. EKS550	Multi-Layer Hi-Resolution Mixer seamless Switcher with 10 inputs and 3 operating modes
 <ul style="list-style-type: none"> 3 operating modes: Mixer, Native Matrix and Quadravision modes Advanced Native Matrix mode Up to 4 layers on Frame Background in Quadravision mode 	<ul style="list-style-type: none"> Transitions: Stretch, Circle, Depth & Flip Mirror effect

1 PRW 10 IN 2 OUT 2U size



Orchestra ² - Ref. ORC50	Powerful intuitive and Ergonomic Controller for Rental and Staging/Multi-venues/Integration
 <ul style="list-style-type: none"> Controls simultaneously up to 6 screens in single or multiple display configuration Controls a large number of Analog Way's seamless Switchers Can store up to 64 presets per screen selection 	<ul style="list-style-type: none"> T-Bar for smooth manually controlled transitions Joystick for easy and fast set up of images or effect parameters

4-line VFD

References	Eikos ² Ref. EKS550	Saphyr Ref. SPX450	Pulse ² 3G Ref. PLS350-3G	QuickVu 3G Ref. QVU150-3G
OPERATION MODE	3	2	2	1
Mixer mode	✓	✓	✓	✓
8 x 2 Native Matrix mode				
10 x 2 Native Matrix mode	✓ (Advanced)	✓ (Medium)		
Quadravision	✓			
INPUTS	10	10	8	8
Universal Analog plugs	4	4	4	4
HDMI plugs	4	4	4	4
Single Link DVI-D plugs	4 (HDMI compatible)	4 (HDMI compatible)	4 (HDMI compatible)	4 (HDMI compatible)
3G/HD/SDI plugs	4	4	2	2
Max. resolution	2K / 2048x1152	2K / 2048x1152	2K / 2048x1152	2K / 2048x1152
Universal analog input EDID	4	4	4	4
EDID (DVI - HDMI-DisplayPort)	8 (All plugs)	8 (All plugs)	8 (All plugs)	8 (All plugs)
HDCP Compliance(DVI - HDMI)	✓	✓	✓	✓
PROGRAM OUTPUTS	2	2	2	2
Universal Analog plug	✓	✓	✓	✓
Single Link DVI-I plug	✓	✓	✓	✓
3G/HD/SDI plug	✓	✓	✓	✓
Computer formats	✓	✓	✓	✓
HDTV formats	✓	✓	✓	✓
Max resolution	2K / 2048x1152	2K / 2048x1152	2K / 2048x1152	2K / 2048x1152
EDID detection (Analog & DVI)	✓	✓	✓	✓
HDCP Compliance	✓	✓	✓	✓
VIDEO OUTPUT	1	1	0	0
CVBS	✓	✓		
Y/C	✓	✓		
Components (YPbPr, RGBS)	✓	✓		
3G/HD/SDI plug	✓	✓		
SDTV/EDT formats	✓	✓		
HDTV formats	✓	✓		
Max resolution	2K / 2048x1152	2K / 2048x1152		
HDCP Compliance	✓	✓		
MATRIX MODE LAYERS				
Background frame layer	1	1		
Native Background layer (Not scaled)	1	1		
Fully resizable Layers	2	1 (True seamless)		
Foreground logo layers	1	1		
TRANSITION & EFFECTS				
Cut	✓	✓	✓	✓
Clean-cut	✓	✓	✓	✓
Fade	✓	✓	✓	✓
Slide	✓	✓	✓	✓
Wipe	✓	✓	✓	✓
Stretch	✓			
Circle	✓			
Flying layer	✓	✓	✓	✓
Flying zoom	✓	✓	✓	✓
Mirror Effect	✓			
Smooth Move	✓	✓	✓	✓
FRAME & LOGO				
Available frames	8	8	8	8
Available logos (animated logo)	8 (1)	8 (1)	8 (1)	8 (1)
AUDIO INPUTS				
Analog stereo inputs	4 Balanced	4 Balanced	4 Balanced	4 Balanced
S/PDIF inputs	2	2	2	2
SDI input audio de-embedding	✓	✓	✓	✓
HDMI input audio de-embedding	✓	✓	✓	✓
AUDIO OUTPUTS				
Analog stereo output (Balanced/UnBalanced)	Program (B) + Prelist (B)	Program (B) + Prelist (B)	Program (B) + Prelist (B)	Program (B) + Prelist (B)
S/PDIF stereo outputs	Program + Prelist	Program + Prelist	Program + Prelist	Program + Prelist
HDMI output audio embedding (DVI plug)	✓	✓	✓	✓
PROCESSING				
Stochastic adaptative hybrid de-interlacer	✓	✓	✓	✓
Auto Centering	✓	✓	✓	✓
Aspect ratio	✓	✓	✓	✓
Freeze	✓	✓	✓	✓
Luma/Chroma key	✓ (Basic)	✓ (Basic)	✓ (Basic)	✓ (Basic)
Zoom/Shrink/Crop	✓	✓	✓	✓
DYNAMIC FIT	✓	✓	✓	✓
HUMAN MACHINE INTERFACE				
Front panel display	4-line VFD	4-line VFD	4-line VFD	4-line VFD
RCS ² (Remote Control Software)	✓	✓	✓	✓
Remote Keypad RK-350	✓	✓	✓	✓
Remote Controller ORC50	✓	✓	✓	✓
Shot Box Ref. SB-80	✓	✓	✓	✓
FORM FACTOR				
Rack width	19"	19"	19"	19"
Enclosure	2U	2U	2U	2U
Rack mount kit supplied	✓	✓	✓	✓

RK-350 - Ref. RK-350	Remote Control Keypad designed to control Analog Way's seamless Switchers
 <ul style="list-style-type: none"> User-friendly Remote Control Keypad Compatible with all Midra series Mini-Joystick for easy element control Large VFD Display offering high contrast menu 	<ul style="list-style-type: none"> Direct layers, logos, frames and sources selection Mini T-bar to control effect level

Accessories & Tools

VIO 4K

LiveCore™ Output Expander 16 Ref. LOE016-4K



Expansion module gives 4 additional Program outputs and 1 Operator/Aux output for SmartMatriX Ultra & Ascender 16

- 2 true-seamless scaled layers + 1 native background layer per output
- 4 outputs
- Output format up to 4K@30p 4:4:4, 4K@60Hz 4:2:0 on HDMI plug & four quadrant 4K@60Hz 4:4:4
- 4K frames support
- Heterogenous Link support

- Independent Preview/Mosaic/Monitoring output
- Full Preview of any sources of the linked chassis (Preview/Mosaic/Monitoring)
- Customization of monitoring layouts (Up to 8 templates stored)
- Advanced Layer management
- Rotation capability in output (Step by 90°)
- Ruggedized and heavy-duty design

1 PRW 4 OUT 4U size



LiveCore™ Output Expander 32 Ref. LOE032-4K



Expansion module gives 4 additional Program outputs and 1 Operator/Aux output for Ascender 32

- 4 true-Seamless scaled layers + 1 native background layer per output

1 PRW 4 OUT 4U size



LiveCore™ Output Expander 48 Ref. LOE048-4K



Expansion module gives 4 additional Program outputs and 1 Operator/Aux output for Ascender 48

- 6 true-Seamless scaled layers + 1 native background layer per output
- Option: Perspective Layer upgrade

1 PRW 4 OUT 4U size

Secure Power Unit - Ref. SPU001



Innovative External Power Accessory for select LiveCore™ Switchers

- Power protection module for select LiveCore™ devices
- Dual power supplies provide redundancy against branch circuit failure
- Battery module secures against mains loss or unstable power

AW Screen Frame Cutter



Free tool to split any wide-screen image into multiple still backgrounds for your multi-projector Soft Edge Blending

- Configure the Soft Edge horizontal/vertical size
- Configure projectors resolution
- Configure image settings (size, position & background color)
- Input formats supported: BMP, JPG, PNG, TIFF and GIF
- Output format: PNG
- Simple and intuitive user interface
- Available for Windows & Mac OS

Shot Box & Control Box



Cost effective solution to easily control the main commands on the LiveCore™ & Midra™ series

Ref. SB-80




Ref. SB124-T

- 76 (SB-80) / 99 (SB124-T) function-labeled keys
- T-Bar to control manually transitions (SB124-T)
- Addressable blue and red backlighting
- Instantly usable for LiveCore™ series (External Software supplied)
- Instantly usable for Midra™ series* (Direct control from the RCS² software)
- USB connection to PC or Mac
- Includes USB controller, carrying case and Software fees

* Only for Ref. SB-80

VIO 4K - Ref. V701

The Ultimate Video Processing Tool Box



7 IN 3 OUT 2U size

VIO 4K at a glance

- The «All in One» solution for any conversion
- User-friendly and Intuitive Graphic Interface
- Diverse selection of option cards for video and audio system expansion
- Advanced LED Wall functionalities
- 10-bit processing 4:4:4



Option

- **OPT-4K60P-VIO4K:** DP1.2 and HDMI 2.0 - I/O Expansion Interface (Available Q4 2016)
- **OPT-AUDIOXLR-VIO4K:** AES/EBU & i3D Digital Audio (XLR) & Analog Stereo balanced audio (XLR) - I/O Expansion Interface

Key features

- Up to 9 inputs and 3 independent outputs
- 2 slots for video option card system expansion
- 1 slot for audio option card system expansion
- The source can be positioned anywhere on the screen, and up to 100% outside the screen in any direction
- Easy Area Of Interest management
- Genlock + Loopthrough: Tri-level Sync. (HD) and Black Burst (SD)
- All Genlock timings meet broadcast ITU/SMPTE standards
- Output rotation: 90°, 180° and 270° per output
- Unlimited zooming and shrinking
- Live monitoring of sources on the large 3.5" Color TFT LCD Display
- Cross hatch, Dynamic Pattern
- New audio management: 8 channels up to 96kHz (Digital audio, AES & 3id)
- Audio Delay compensation up to 300ms
- Fast swappable DVI I/O boards
- Memory space for frames in 4K (up to 2 directly accessible by the screen)
- USB Host: mass storage
- USB Device link

The "All in One" selection for any conversion



The expansion interfaces are shown here as an example of options

Anything In

- Composite (PAL, NTSC)
- S-Video
- YUV (Y CB Cr)
- Computer (RGBHV, RGBS, RGsB)
- HD-YUV (HD-YCrCb)
- HD-RGB
- DVI
- DisplayPort
- HDMI
- HD/SD-SDI
- 3G-SDI
- 6G-SDI* (Compliant Level A & B)
- 12G-SDI (Expansion Interface)
- Digital Audio: AES/EBU & i3d (Expansion Interface)

- Analog Audio Stereo
- Digital Audio
- 1080P/1080i
- 720P
- 480P/480i
- 2K/1080p
- WUXGA (1920x1200@60Hz)
- WQXGA (2560x1600@60Hz)

- UHD (3840x2160@30Hz)
- 4K (4096x2160@30Hz)
- Ultra High Resolution up to 4K@60P (Expansion Interface)

*Available Q4 2016

Anything Out

Universal system for format conversion

- Upward conversion (Scaler)
- Downward conversion (Scan Converter)
- Transcoder
- Coder
- Aspect ratios
- Multi-format Analog Genlock
- Dynamic Test Patterns
- Pan & Zoom function
- Freeze Frame

- Aperture correction
- Advanced LED Wall functionalities
- Audio and Video monitoring directly from the front panel
- Output rotation

- Custom Formats
- EDID Management
- Genlock/Framelock
- Gamma correction & Color Temperature settings



www.analogway.com

Analog Way SAS - Headquarters

2/4 rue Georges Besse
92160 Antony
FRANCE
Tel.: +33 (0)1 81 89 08 60

Analog Way Germany

Tel.: +49 7161 5075668

Analog Way Inc.

3047 Summer Oak Place
Buford, GA 30518
USA
Tel.: +1 212 269 1902

Analog Way Italy

Tel.: +39 02 39493943

Analog Way Pte Ltd

152 Beach Road
#15-03 Gateway East
SINGAPORE 189721
Tel.: +65 6292 5800

Analog Way UK

Tel.: +44 (0)7 913 993 182

Connect with us on

